





Performance



Reliability



Productivity



Компания СинЭкс (ТМ ТИРИТ)
является официальным представителем
Teledyne Isco в России
www.tirit.org
(495) 223-18-03

Table of Contents

● RediSep® Rf Column Overview.....	2
● RediSep Rf Gold High Performance Flash Chromatography	3 & 4
● RediSep Rf Normal Phase Silica Columns & TLC Plates.....	5
● RediSep Rf Gold® Normal Phase Silica Columns	6
● Column Media Selection Guide	7
● Stationary Phase Polarity	7
● RediSep Rf C18 Columns & TLC Plates	8
● RediSep Rf Gold C18 Columns.....	9
● RediSep Rf Gold C18Aq Columns.....	10
● RediSep Rf Gold Amine Columns & TLC Plates	11
● RediSep Rf Gold Cyano Columns	12
● RediSep Rf Gold Diol Columns & TLC Plates.....	12
● RediSep Rf Alumina Columns & TLC Plates.....	13
● RediSep Rf Strong Anion Exchange (SAX) Columns	14
● RediSep Rf Strong Cation Exchange (SCX) Columns.....	14
● RediSep Solid Load Cartridges.....	15
● Bulk RediSep Media Chart.....	16
● Self-pack Flash Column Kits.....	16
● RediSep Library.....	17
● CombiFlash Systems.....	18

Компания СинЭкс (ТМ ТИРИТ) является официальным представителем в РФ
www.tirit.org || (495) 223-18-03



RediSep® Rf Column Overview

Teledyne Isco's reliable RediSep Rf preparative chromatography products are designed to consistently produce high purity compounds. You'll enjoy fast, easy purification and scale-up from milligram to hundreds of grams.

Reliable and Reproducible

RediSep Rf columns are precision-packed for high resolution and reproducibility. They feature a one-piece design with luer end fittings for quick, easy connection to Teledyne Isco CombiFlash® and other chromatography systems. RediSep Rf sets the standard in Flash chromatography columns.

Versatile


RediSep Rf columns are available in 4 gram up to 3 kg column sizes allowing purification from 10 milligrams up to 300 grams. The enhanced product offering with high performance Gold and new stationary phases expands the utility of RediSep Rf. A wide offering of TLC plates makes method development easy.

RFID Confidence

Through RFID technology, the CombiFlash Rf+ and Torrent® systems automatically detect the column type and size and programs a default method optimized for the RediSep column. Method automation reduces setup time and the potential for errors.

Safe

Extra thick walls on the RediSep Rf columns and cartridges are pressure rated for safe operation. Machine welded end fittings ensure the column is able to withstand the pressure capability of modern flash systems and not leak valuable compound.



U.S. Patent # 7,008,541. EU Patent # 1,316,798. Other patents pending.

RediSep Rf Gold[®]

High Performance Flash Chromatography

Resolution with Speed

As a pioneer in Flash chromatography, Teledyne Isco continues to bring you the latest innovations to improve your productivity. RediSep Rf Gold high performance Flash columns deliver superior sample purity through the use of fine spherical silica gel (20 – 40 μm).

RediSep Rf Gold spherical silica provides improved performance without increasing the back pressure. Spherical packing creates the best possible linear beds for even separations. Spherical silica is available bare, and bonded with C18, amine, diol, and cyano.





U.S. patent 7,776,220 granted.
European patent 1,316,798 granted.

Gold Resolution – $\Delta Rf \leq 0.1$

Improve your resolution with smaller particles. Patented spherical Flash media creates the benefit of tighter packing without an increase in back pressure.

- Provide twice the resolving power of typical disposable Flash chromatography columns.
- Separate difficult compounds with low ΔRf , such as isomers or trace compounds
- Purify your tough compounds on a single column



Run Conditions:


Column size:	40 g
Load:	333 mg (on 5 g cartridge)
Solvents:	Hexane & Ethyl Acetate
Flow rate:	40 mL/min
Run time:	19.4 min

See Application Note AN70 at
www.isco.com/products/lcappnotes.asp
for complete information.

Gold Speed – $\Delta Rf > 0.1$

Take advantage of the sharper peaks provided by spherical media to shorten purification time. Convert your methods to Gold Speed at a click of a button with PeakTrak® software.

- Save up to 60% on time and 30% on solvents
- Separate silica sensitive compounds faster
- Dry compounds faster by collecting in 2/3 -fewer fractions




Run Conditions:

Column size:	40 g
Load:	0.4 g (1% load)
Solvents:	Hexane & Ethyl Acetate
Flow rate:	40 mL/min, 80 mL/min

See Application Note AN72 at www.isco.com/products/lcappnotes.asp for complete information.

Gold High Load

Take advantage of the extra resolution to load twice as much compound on the RediSep Rf Gold column. Choose a smaller column size and save time and solvent.




Run Conditions:

Column size:	12 g spherical RediSep Rf Gold, 12 g irregular non-RediSep
Loads:	0.02 – 0.80 g (0.2 – 7% load)
Solvents:	Hexane & Ethyl Acetate

See poster reprint “Spherical Silica Increases Loading Capacity” at www.isco.com/products/lcappnotes.asp for complete information.




The RFID Advantage



Simply select between Gold Resolution and Gold Speed methods on CombiFlash systems with RFID.

RediSep® Rf Normal Phase Silica

RediSep Rf disposable, bare silica columns for Flash purification of organic compounds are the benchmark for normal phase separations. This high quality media is specified for high resolution and reproducibility for everyday purifications.



Specifications:

- Reusability: Single use
- Particle size: 40 – 63 µm irregular
- Mesh size: 230 – 400
- Pore size: 60 Å
- Surface area m²/g: 500 ±50
- Loading capacity: 0.1 – 10%

RediSep Rf Normal Phase Disposable Flash Columns, 40 – 60 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV ≤ 1	ΔCV ≥ 6				
20 mg	0.4 g	4 g	20	18	69-2203-304
60 mg	1.2 g	12 g	20	30	69-2203-312
120 mg	2.4 g	24 g	15	35	69-2203-324
200 mg	4 g	40 g	15	40	69-2203-340
400 mg	8 g	80 g	12	60	69-2203-380
600 mg	12 g	120 g	10	85	69-2203-320
Filter	12 g	125 g	6	200	69-2203-314
1.1 g	22 g	220 g	6	150	69-2203-422
1.65 g	33 g	330 g	4	200	69-2203-330
3.8 g	75 g	750 g	4	300	69-2203-275
7.5 g	150 g	1.5 kg	3	600	69-2203-277
15 g	300 g	3.0 kg	1	950	69-2203-527

Sample Loading — ΔR_f or ΔCV?

This catalog provides sample loading recommendations in ΔCV (column volumes). Here's how:

- ΔR_f values are inversely proportional to the elution time of a component from a column as shown by:

$$CV = 1/R_f$$

- ΔCV can be determined using the following formula:

$$\Delta CV = 1/R_{f1} - 1/R_{f2}$$

- ΔCV is a better predictor for cartridge separations

Greater sample loads are possible with easy separations, or those with a ΔCV ≥ 6. As the ΔCV approaches ≤ 1, the separation becomes more difficult, necessitating lesser sample loading on the column or choosing a RediSep Rf Gold high resolution column.



Normal Phase TLC Plates

5 x 10 cm, box of 200..... 69-2203-400

RediSep Rf Gold® Normal Phase Silica


RediSep Rf Gold high performance Flash columns deliver superior sample purity through the use of fine spherical silica gel (20–40 µm). RediSep Rf Gold normal phase silica offers the capability to improve resolution and isolate difficult compounds such as isomers and impurities. Alternatively, the improved resolution solvents can allow for faster run times or higher loads to save time and solvents.

Specifications:


- Reusability: Single use
- Particle size: 20 – 40 µm spherical
- Mesh size: 400 – 632
- Pore size: 60 Å
- Surface area m²/g: 500 ±50
- Loading capacity: 0.1 – 1% Gold Resolution
1 – 10% Gold Speed
2 – 20% Gold High Load

RediSep Rf Gold Normal Phase Silica Columns, 20–40 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
20 mg	0.4 g	4 g	14	18	69-2203-344
60 mg	1.2 g	12 g	14	30	69-2203-345
120 mg	2.4 g	24 g	10	35	69-2203-346
200 mg	4 g	40 g	10	40	69-2203-347
400 mg	8 g	80 g	6	60	69-2203-348
600 mg	12 g	120 g	6	85	69-2203-349
1.1 g	22 g	220 g	4	150	69-2203-359
1.65 g	33 g	330 g	3	200	69-2203-369
3.8 g	75 g	750 g	3	300	69-2203-427
7.5 g	150 g	1.5 kg	2	600	69-2203-428
15 g	300 g	3.0 kg	1	950	69-2203-529




Column Media Selection Guide



40–60 μm irregular media RediSep Rf columns.
 20–40 μm spherical media RediSep Rf Gold® high performance columns.


Stationary Phase Polarity



Contact Teledyne Isco for custom adapters to use RediSep Rf columns on non-CombiFlash® systems.

RediSep® Rf C18

Teledyne Isco RediSep Rf C18 Reversed-phase columns save time and money for the purification of medium to high polarity as well as ionic compounds. Packed with C18-derivatized silica, RediSep Rf Reversed-phase columns provide reproducible, high-capacity purification without the cost and complexity of prep-HPLC.



Specifications:

- Reusability: 20 runs (average)
- Particle size: 40 – 63 µm irregular
- Mesh size: 230 – 400
- Pore size: 60 Å
- Surface area m²/g: 500 ±50
- Carbon Content: >17%
- Endcapped: Yes
- Loading capacity: 0.1 – 2%

RediSep Rf C18 Columns 40 – 60 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
4.3 mg	86 mg	4.3 g	2	18	69-2203-410
13 mg	260 mg	13 g	1	30	69-2203-411
26 mg	520 mg	26 g	1	35	69-2203-412
43 mg	860 mg	43 g	1	40	69-2203-413
86 mg	1.72 g	86 g	1	60	69-2203-416
130 mg	2.6 g	130 g	1	85	69-2203-414
240 mg	4.8 g	240 g	1	150	69-2203-418
360 mg	7.2 g	360 g	1	200	69-2203-415



C18 TLC Plates

Reversed-phase C18 TLC Plates..... 69-2203-586

Plates may also be used for RediSep Rf Gold C18 and RediSep Rf Gold C18Aq method development.



Storage Instructions for All C18 Columns

Proper storage will allow RediSep Rf C18, RediSep Rf Gold® C18, and RediSep Rf Gold C18Aq columns to be reused:

- Never allow the column to dry out after use. Turn off the air purge on instrument.*
- Remove all organic modifiers by flushing the column with 3 column volumes of 80% methanol or acetonitrile in water.
- Store the column in flush solvent with end caps in place.

*CombiFlash® Rf and Torrent systems will turn off the column air purge as needed by reading the column RFID tag.

● RediSep Rf Gold® C18

RediSep Rf Gold C18 Reversed-phase columns are packed with 20–40 µm spherical bonded silica, providing improved separation. Achieve near prep-HPLC results with greater sample recovery to easily purify up to gram-scale on your Flash system. The end-capped C18 chains allow up to 20 separations at pH 10 without destroying the silica.

Specifications:

- Reusability: 20 runs (average)
- Particle size: 20 – 40 µm spherical
- Mesh size: 400 – 632
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Carbon content: 15% ±2
- Endcapped: Yes
- Loading capacity: 0.1 – 2%

RediSep Rf Gold C18 Columns 20–40 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
5.5 mg	110 mg	5.5 g	2	18	69-2203-328
15.5 mg	310 mg	15.5 g	1	30	69-2203-334
30 mg	600 mg	30 g	1	35	69-2203-335
50 mg	1.0 g	50 g	1	40	69-2203-336
100 mg	2 g	100 g	1	60	69-2203-337
150 mg	3 g	150 g	1	85	69-2203-338
275 mg	5.5 g	275 g	1	150	69-2203-339
415 mg	8.3 g	415 g	1	200	69-2203-341
0.95 g	19 g	950 g	1	180	69-2203-492
1.9 g	38 g	1.9 kg	1	260	69-2203-493
3.8 g	76 g	3.8 kg	1	360	69-2203-528



RediSep Rf Gold® C18Aq

RediSep Rf Gold C18Aq is especially designed for highly aqueous conditions. Monofunction C18 bonding is interspersed with hydrophilic ligands to prevent phase collapse in high aqueous conditions. RediSep Rf Gold C18Aq should be used in separations requiring 0–50% organic. These columns are useful for highly polar, water soluble compounds such as dyes, glycopeptides, and nucleotides.

Specifications:


- Reusability: 20 runs (average)
- Particle size: 20 – 40 µm spherical
- Mesh size: 400 – 632
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Carbon content: 11% ±2
- Endcapped: Yes
- Loading capacity: 0.1 – 2%

RediSep Rf Gold C18Aq Columns 20–40 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
5.5 mg	110 mg	5.5 g	2	18	69-2203-558
15.5 mg	310 mg	15.5 g	1	30	69-2203-559
30 mg	600 mg	30 g	1	35	69-2203-560
50 mg	1.0 g	50 g	1	40	69-2203-561
100 mg	2 g	100 g	1	60	69-2203-562
150 mg	3 g	150 g	1	85	69-2203-563
275 mg	5.5 g	275 g	1	150	69-2203-564
415 mg	8.3 g	415 g	1	200	69-2203-565
0.95 g	19 g	950 g	1	180	69-2203-566
1.9 g	38 g	1.9 kg	1	260	69-2203-567
3.8 g	76 g	3.8 kg	1	360	69-2203-568



C18 Silica Phase Collapse/Dewetting



RediSep Rf Gold[®] Amine

RediSep Rf Gold Amine columns can be used in either normal or reversed-phase conditions for the purification of compounds with basic properties by interacting with the hydrogen bonds. Functionalized amine silica protects the acidic silanol groups to result in sharper peaks and purity.

Useful in the separation of drug intermediates such as those with adenine, pyridine, or aniline groups. Use bonded amine to purify 2°, 3°, and heterocyclic amines without using dichloromethane. Amine media also eliminates the need to add a mobile phase modifier such as TEA, which reduces the time required to remove solvent from purified fractions.

Use caution when purifying aldehydes and ketones which may react with amine side chains to form imines. Test a small amount on a small column.



Specifications:


- Reusability: 20 runs (average)
- Particle size: 20 – 40 µm spherical
- Mesh size: 400 – 632
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Loading capacity: 0.1 – 2%

RediSep Rf Gold Amine Columns 20 – 40 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
5.5 mg	110 mg	5.5 g	2	18	69-2203-504
15.5 mg	310 mg	15.5 g	1	30	69-2203-505
30 mg	600 mg	30 g	1	35	69-2203-506
50 mg	1.0 g	50 g	1	40	69-2203-507
100 mg	2 g	100 g	1	60	69-2203-508
150 mg	3 g	150 g	1	85	69-2203-509
275 mg	5.5 g	275 g	1	150	69-2203-510
415 mg	8.3 g	415 g	1	200	69-2203-511
0.95 g	19 g	950 g	1	300	69-2203-512
1.9 g	38 g	1.9 kg	1	600	69-2203-513
3.8 g	76 g	3.8 kg	1	950	69-2203-534

RediSep Gold Amine TLC Plates

5 x 10 cm, box of 50, with F254 indicator 69-2203-573



Storage Instructions for Amine, Cyano, and Diol Columns

Proper storage will allow amine, cyano, and diol columns to be reused:

- Do not allow the column to dry out after first use. Turn off the air purge on instrument.*
- If run solvents are immiscible with storage solvents, wash the column with an intermediate solvent.
- Remove all organic modifiers or strong organic solvents by flushing the column with 3 column volumes of:
 - **Amine and Diol columns:** 80% acetonitrile in water or 100% isopropanol.
 - **Cyano columns:** 80% methanol or acetonitrile in water or 100% isopropanol.
- Store the column in flush solvent with end caps in place.

*CombiFlash[®] Rf and Torrent systems will turn off the column air purge as needed by reading the column RFID tag.

RediSep Rf Gold® Cyano

RediSep Rf Cyano columns have a cyano bound silica gel. Cyano functionality creates a slightly hydrophobic nature, and has different selectivity. Cyano may be used in either normal or reversed-phase conditions. Cyano is always the least retentive media in either normal or reversed phase conditions, making it ideal for extremely polar compounds.



Specifications:

- Reusability: 20 runs (average)
- Particle size: 20 – 40 µm spherical
- Mesh size: 400 – 632
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Loading capacity: 0.1 – 2%


RediSep Rf Gold Cyano Columns 20 – 40 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
5.5 mg	110 mg	5.5 g	2	18	69-2203-494
15.5 mg	310 mg	15.5 g	1	30	69-2203-495
30 mg	600 mg	30 g	1	35	69-2203-496
50 mg	1.0 g	50 g	1	40	69-2203-497
100 mg	2 g	100 g	1	60	69-2203-498
150 mg	3 g	150 g	1	85	69-2203-499
275 mg	5.5 g	275 g	1	150	69-2203-500
415 mg	8.3 g	415 g	1	200	69-2203-501
0.95 g	19 g	950 g	1	300	69-2203-502
1.9 g	38 g	1.9 kg	1	600	69-2203-503
3.8 g	76 g	3.8 kg	1	950	69-2203-533

RediSep Rf Gold® Diol

RediSep Rf Gold Diol functionalized silica gel behaves similar to bare silica by forming hydrogen bonds and is a good reusable option. Diol is neutral and less polar with greater retention times than bare silica. This media offers an alternative for separations of low to medium polarity compounds.

Care should be taken with ketones and also 1° and 2° amine compounds or solvents.



Specifications:

- Reusability: 20 runs (average)
- Particle size: 20 – 40 µm spherical
- Mesh size: 400 – 632
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Loading capacity: 0.1 – 2%



RediSep Rf Gold Diol Columns 20 – 40 micron

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
ΔCV≤1	ΔCV≥6				
5.5 mg	110 mg	5.5 g	2	18	69-2203-514
15.5 mg	310 mg	15.5 g	1	30	69-2203-515
30 mg	600 mg	30 g	1	35	69-2203-516
50 mg	1.0 g	50 g	1	40	69-2203-517
100 mg	2 g	100 g	1	60	69-2203-518
150 mg	3 g	150 g	1	85	69-2203-519
275 mg	5.5 g	275 g	1	150	69-2203-520
415 mg	8.3 g	415 g	1	200	69-2203-521
0.95 g	19 g	950 g	1	300	69-2203-522
1.9 g	38 g	1.9 kg	1	600	69-2203-523
3.8 g	76 g	3.8 kg	1	950	69-2203-535

RediSep Gold Diol TLC Plates

5 x 10 cm, box of 50, with F254 indicator 69-2203-574

RediSep® Rf Alumina

Single use alumina columns run under normal phase conditions and offer different selectivity to silica. Neutral alumina columns are useful when samples are acid sensitive and prone to degradation on normal phase silica gel.

Use acidic alumina to purify acidic compounds without adding modifiers such as acetic acid. Choose basic alumina to purify basic compounds without basic modifiers such as TEA or ammonium hydroxide. This avoids solvent swapping, washing the chromatography system, or contaminating subsequent runs.



Specifications:

- Reusability: Single use
- Particle size: 40 – 63 µm irregular
- Mesh size: 230 – 400
- Pore size: 60 Å
- Surface area m²/g: 200 ±50
- pH: Acidic 4.5 ±0.4
Neutral 7.0
Basic 9.7 ±0.3
- Loading capacity: 0.5 – 4%



RediSep Rf Alumina Columns

Sample Load		Size	Qty/Pkg	Flow Rate (mL/min)	Acidic Cat. # 69-2203-	Neutral Cat. # 69-2203-	Basic Cat. # 69-2203-
ΔCV≤1	ΔCV≥6						
40 mg	320 mg	8 g	20	18	430	440	450
120 mg	960 mg	24 g	20	30	431	441	451
240 mg	1.92 g	48 g	15	35	432	442	452
400 mg	3.2 g	80 g	15	40	433	443	453
800 mg	6.4 g	160 g	12	60	436	446	456
1.2 g	9.6 g	240 g	10	85	434	444	454
2.2 g	17.6 g	440 g	6	150	438	448	458
3.3 g	26.4 g	660 g	4	200	435	445	455

RediSep Rf Alumina TLC Plates

Neutral, 5 x 10 cm, box of 30, with F254 indicator 69-2203-569
Basic, 5 x 10 cm, box of 30, with F254 indicator 69-2203-403



Strong anion exchange (SAX) silica gel fully retains acidic compounds. SAX columns can be used as a clean-up tool or to isolate acidic products. They work as a catch and release process.

RediSep Rf SAX Columns

Sample Load†	Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
≤6.27 mmol	5.7 g	2	18	69-2203-381
≤18.7 mmol	17 g	1	30	69-2203-382
≤37.4 mmol	34 g	1	35	69-2203-383
≤62.7 mmol	57 g	1	40	69-2203-384
≤125.4 mmol	114 g	1	60	69-2203-387
≤187 mmol	170 g	1	85	69-2203-385
≤344.3 mmol	313 g	1	150	69-2203-389
≤517 mmol	470 g	1	200	69-2203-386

†Sample load = mmol x compound molecular weight/1000.


RediSep® Rf SCX

Strong cation exchange (SCX) silica gel fully retains basic compounds. SCX columns can be used as a clean-up tool or to isolate basic products. They work as a catch and release process.

RediSep Rf SCX Columns

Sample Load†	Size	Qty/Pkg	Flow Rate (mL/min)	Catalog #
≤3.5 mmol	5 g	2	18	69-2203-390
≤10.5 mmol	15 g	1	30	69-2203-391
≤21 mmol	30 g	1	35	69-2203-392
≤35 mmol	50 g	1	40	69-2203-393
≤70 mmol	100 g	1	60	69-2203-396
≤105 mmol	150 g	1	85	69-2203-394
≤192 mmol	275 g	1	150	69-2203-398
≤287 mmol	410 g	1	200	69-2203-395

†Sample load = mmol x compound molecular weight/1000.



Specifications:

- Reusability: 20 runs (average)
- Particle size: 40 – 63 µm spherical
- Mesh size: 230 – 400
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Loading capacity: 0.8 ±0.2 mmol/g


Storage Instructions for SAX & SCX Columns

Proper storage will allow SAX & SCX columns to be reused:

- Never allow the column to dry out after first use. Turn off the air purge on instrument.*
- Regenerate the column with:
 - **SAX Column:** 10 column volumes of 5% NH₄OH in methanol.
 - **SCX Column:** 10 column volumes of 1M acetic acid in methanol.
- Flush with 10 column volumes of 80% methanol in water or 100% isopropanol.
- Store the column in flush solvent with end caps in place.

Depending on your sample, the column activity may decrease during use.

*CombiFlash® Rf and Torrent systems will turn off the column air purge as needed by reading the column RFID tag.



Specifications:

- Reusability: 20 runs (average)
- Particle size: 40 – 63 µm spherical
- Mesh size: 230 – 400
- Pore size: 100 Å
- Surface area m²/g: 300 ±50
- Loading capacity: 0.8 ±0.2 mmol/g

RediSep® Solid Load Cartridges

RediSep solid load cartridges improve the resolution of the compound and eliminate reaction byproducts when compared to liquid injection techniques. Prepare pre-filled solid load cartridges by pipetting the dissolved sample onto the top of the cartridge. Prepare empty solid load cartridges by filling the cartridge with a slurry mixture of the dissolved sample and supporting media. For optimal benefits, remove the solvent by vacuum before placing the cartridge on the purification system.

Adjustable Solid Load Cartridge Cap (SLCC)

For use with RediSep sample load cartridges.
 Fits 2.5 and 5 gram sample load cartridges.
 For use on CombiFlash® Rf systems.....60-5237-047
 Fits 12 and 25 gram sample load cartridges.
 For use on CombiFlash Rf
 and Torrent® systems60-5237-048
 Fits 32 and 65 gram sample load cartridges.
 For use on CombiFlash Rf
 and Torrent systems.....60-5237-044
 Fits 130 and 260 gram sample load cartridges.
 For use on CombiFlash Torrent systems60-5247-008
 Fits 375 and 750 gram sample load cartridges.
 For use on CombiFlash Torrent systems60-5247-009

Empty Disposable Sample Load Cartridges

Size	Qty	Catalog #
5 g	30	69-3873-235
25 g	30	69-3873-240
65 g	12	69-3873-225
260 g	6	69-3873-201
750 g	4	69-3873-224

Prepacked Disposable Sample Load Cartridges

Size	Normal Phase Silica		Celite		C18	
	Qty	Cat. # 69-3873-	Qty	Cat. # 69-3873-	Qty	Cat. # 69-3873-
2.5 g	20	238	20	312	5	247
5 g	20	236	20	313	5	237
12 g	15	243	15	314	4	248
25 g	15	241	15	315	4	242
32 g	12	310	12	318	3	249
65 g	12	226	12	319	3	250
125 g	4	311				
260 g	4	202				
375 g	4	229				
750 g	4	231				



Cartridge Dryer

Solid Load Cartridge Dryer
 Includes adapters for Rf cartridges60-2200-010

Bulk RediSep® Media

Media	Particle	Container Size	Catalog Number
Silica	63 – 200 µm irregular	450 g	60-3874-091
		950 g	60-3874-045
		25 kg	60-3874-047
Silica	40 – 63 µm irregular	950 g	60-5394-478
		25 kg	60-5394-479
Gold Silica	20 – 40 µm spherical	950 g	60-5394-480
		25 kg	60-3874-055
C18	40 – 63 µm irregular	450 g	60-5394-499
		950 g	60-5394-482
		25 kg	60-3874-059
Gold C18	20 – 40 µm spherical	450 g	60-5394-498
		950 g	60-5394-481
		25 kg	60-5394-493
Gold C18Aq	20 – 40 µm spherical	450 g	60-5394-507
		950 g	60-5394-508
		25 kg	60-5394-509
Gold Amine	20 – 40 µm spherical	450 g	60-5394-500
		950 g	60-5394-491
		25 kg	60-5394-486
Gold Diol	20 – 40 µm spherical	450 g	60-5394-502
		950 g	60-5394-494
		25 kg	60-5394-495
Gold Cyano	20 – 40 µm spherical	450 g	60-5394-501
		950 g	60-5394-496
		25 kg	60-5394-497
Alumina Acidic	40 – 63 µm irregular	950 g	60-5394-489
Alumina Neutral	40 – 63 µm irregular	950 g	60-5394-488
Alumina Basic	40 – 63 µm irregular	950 g	60-5394-487
SCX	40 – 63 µm spherical	450 g	60-5394-504
SAX	40 – 63 µm spherical	450 g	60-5394-503



Self-pack Flash Column Kits

Self-pack column kits allow use of the reusable RediSep Rf cartridges in place of a column. Each kit includes a solid load cartridge cap, one package of empty cartridges with frits, and bulk silica gel, 40 – 60 µm.

- 1 – 5 gram kit with 950 grams bulk silica gel60-3877-206
- 5 – 25 gram kit with 1900 grams bulk silica gel60-3877-207*
- 25 – 65 gram kit with 1900 grams bulk silica gel60-3877-208
- 65 – 260 gram kit with 2850 grams bulk silica gel60-3877-209

*To use with CombiFlash Companion systems, purchase external column adaptor, 60-5394-432, extra.

Self-pack Flash Column Kit Accessories

- Package of 150 frits, 5 gram.....60-5237-052
- Package of 100 frits, 25 gram60-5237-053
- Package of 75 frits, 65 gram.....60-5237-054
- Package of 25 frits, 260 gram60-5237-055



RediSep® Library

Teledyne Isco has an extensive library of application notes, posters, and paper reprints. Selected resources are listed below.

Silica ●

AN70, Higher Resolution Results with RediSep Rf Gold® Silica Columns

Poster Reprint, Purification of Carbohydrates by MPLC

Poster Reprint, Spherical Silica Increases Loading Capacity

C18 ●

AN49, Improvements in RP MPLC as Alternative to Prep HPLC

AN51, RediSep C18 Column – Purification of peptides

AN55, RediSep C18 Column – Purification of low-solubility polar heterocycles

Amine ●

AN31, RediSep Amine Column – Purification of high pKa Organic Compounds Case Study 1

Poster Reprint, Advanced Topics RediSep Specialty Media

Cyano ●

AN60, RediSep Neutral Alumina Column – Purification of High pKa Organic Compounds Case Study 1

Poster Reprint, Advanced Topics RediSep Specialty Media

Diol ●

AN27, Rapid Purification of Tocopherols

Poster Reprint, Diol Columns – Pretend They're Normal Phase

SAX ●

AN44, RediSep SAX Column – Purification of acidic compounds with multipurpose scavenger column Case Study 1

SCX ●

AN39, RediSep SCX Column – Purification of High pKa Organic Compounds Case Study 1

Solid Load Cartridges ●

AN15, Dry samples improve resolution in normal phase flash chromatography

Detection Techniques

AN22, Expanded Compound Wavelength Detection with UV-Vis

AN80, Evaporative Light Scattering Detectors

AN81, CombiFlash® All-wavelength Collection

General Information

AN20, Acetone as an Alternative to Ethyl Acetate

Our full library is available online at www.isco.com/lcappnotes



Request your free copy

“Effective Organic Compound Purification — Guidelines and Tactics for Flash Chromatography.”

Visit www.isco.com/flashguide

Rely on CombiFlash®

CombiFlash® Rf+ and Rf+ Lumen

- Driven by intuitive, powerful PeakTrak® software
- Smallest footprint of any automated Flash system
- Real time and Post Run Spectral Display
- RFID technology for columns and racks
- Rf+ Lumen has integrated ELSD in addition to UV or UV-Vis detection



CombiFlash® Rf+ Purlon, Purlon L and Purlon S

- Fractionate on target mass ion(s) or mass range
- Real time and post run spectral data display
- Quickly switch between ESI and APCI ionization probes
- Choose the model that meets your needs
 - Purlon: 50 – 1200 Dalton range, selectable ionization polarity
 - Purlon S: 50 – 1200 Dalton range, auto-switching ionization polarity
 - Purlon L: 50 - 2000 Dalton range, with auto-switching ionization polarity

CombiFlash Torrent®

- Purify 0.5 to 300 grams in a single run
- Up to 1 liter/minute at 100 psi
- Versatile sample, solvent, fraction, and waste options
- Fully-grounded solvent path for safety
- Easily scale up methods from CombiFlash Rf systems



How to Order

Within the USA, RediSep® Rf and CombiFlash® products are sold direct from the factory to the customer, with support from local representatives in many areas. To arrange for a consultation, product demonstration, or other service from your sales representative, just call our toll-free number below.

Phone: (800) 228-4373 (toll-free)

(402) 464-0231

Fax: (402) 465-3022

E-mail: iscoOrders@teledyne.com

} Monday-Friday, 7:30 AM – 5:00 PM Central Time

**Outside the USA and Canada,
contact your Teledyne Isco
dealer or call + 1 402 464 0231**

Teledyne Isco reserves the right to change specifications without notice.

Компания СинЭкс (ТМ ТИРИТ) является официальным представителем в РФ
www.tirit.org || (495) 223-18-03